

MX25 & MX40

Exit light



Features

- › Cost effective and eco friendly:
 - LED Technology
 - Low voltage
 - Low maintenance
 - Self-contained
 - Simple and fast installation
- › Innovative and intelligent:
 - Monitored for highest safety
 - Addressable for individual control and testing
 - Automatic test system for highest safety and comfort

General

- › Tested and approved according to EN60592-2-22, EN1838, EN62034, and EN ISO:7010

Order number

- › 825100 - MX25 Exit light, 1h
- › 825300 - MX25 Exit light, 3h
- › 825302 - MX25 Exit light Black, 3h
- › 840100 - MX40 Exit light, 1h
- › 840300 - MX40 Exit light, 3h
- › 840302 - MX40 Exit light Black, 3h

Related products

- › 3312FLW - Analog base
- › 3312W - Analog base
- › 930040 - Black base for EMEX
- › 80030 - Cable for EMEX 2*2*1 mm 500 meters
- › 910002 - Battery for MX 1h
- › 910008 - Battery for MX 3 h



White



Black



MX25: 390 g
MX40: 705 g



MX25: 102 x 261 x 225 mm
MX40: 102 x 411 x 300 mm



MX25: 25 m
MX40: 40 m



IP41



<95%



0 TO +55 °C



1 hour or
3 hours



2 cd/m²



LED

