

MX25 & MX40 red X

Exit light



Features

- > For safest evacuation possible:
 - Dynamic control of the evacuation routes
 - Minimised risk to enter smoke filled areas
- > Cost effective and eco friendly:
 - LED Technology
 - Low voltage
 - Low maintenance
 - Self-contained
 - Simple and fast installation
- > Innovative and intelligent:
 - Monitored for highest safety
 - Addressable for individual control and testing
 - Automatic test system for highest safety and comfort

General

- > Tested and approved according to EN60592-2-22, EN1838, EN62034, and EN ISO:7010

Order number

- > 825101 - MX25 Exit light, red X, 1h
- > 825301 - MX25 Exit light, red X, 3h
- > 825303 - MX25 Exit light, red X, Black 3h
- > 840101 - MX40 Exit light, red X, 1h
- > 840301 - MX40 Exit light, red X, 3h
- > 840303 - MX40 Exit light, red X, Black 3h

Related products

- > 3312FLW - Analog base
- > 3312W - Analog base
- > 930040 - Black base for EMEX
- > 80030 - Cable for EMEX 2*2*1 mm 500 meters
- > 910002 - Battery for MX 1h
- > 910008 - Battery for MX 3h



White



Black



MX25: 395 g
MX40: 710 g



MX25: 102 x 261 x 225 mm
MX40: 102 x 411 x 300 mm



MX25: 25 m
MX40: 40 m



IP41



<95%



0 TO +55 °C



1 hour or
3 hours



2 cd/m²



LED

